



SMV Touch Panel

L86EE/ L75EE/ L65EE/ L55EE



20pt touch



Dual System



4K HDMI



Note Writing Software



Wireless Projection



Safety Lock

Product Feature

- Front USB port
- Front Physical Key
- Bottom Loudspeaker
- 4K Ultra HK Display
- IR (Infrared Ray) Touch Technology
- AG Tempered Glass 4mm Mohs level 7
- Compatible with detachable PC module

Follow us on



SMV.hk



SMV.hk

Products Specification



Models	L86EE	L75EE	L65EE	L55EE
Display				
Size	86 inch	75 inch	65 inch	55 inch
Response Time	8ms			
Aspect Ratio	16:9			
Display Area	1,895.04(H) × 1,065.96(V)mm	1,649.664(H) × 927.936(V)mm	1,428.48(H) × 803.52(V)mm	1,209.6(H) × 680.4(V)mm
Resolution	3,840(H) × 2,160(V)			
Pixel Pitch	0.4935 × 0.4935mm	0.4296 × 0.4296mm	0.372 × 0.372mm	0.315 × 0.315mm
Refreshing Frequency	60Hz			
Display Color	1.07B (10bit)			
Contrast Ratio	1,200:1	1,100:1	1,200:1	1,200:1
Viewing Angle	178°			
Back Light Unit	DLED			
Brightness with glass (typ)	350cd/m2		300cd/m2	
Brightness with glass (min)	300cd/m2			
Life Time	30,000 Hours			
Video/Audio				
Sound Channel	2.0			
Output Power	2 x 12W			
Display Connectors				
HDMI IN	3			
HDMI OUT	1			
USB 2.0	3 (Including 2 USB ports in front)			
USB 3.0	3			
TOUCH OUT	2			
VGA IN	1			
AUDIO IN	1			
AUDIO OUT	1			
SPDIF	1			
LAN (RJ45)	1			
RS232	1			

Product Specification



Models	L86EE	L75EE	L65EE	L55EE
Touch System				
Sensing Type	Infrared Recognition			
System	Windows 10/ Windows 8/ Windows 7/ Windows XP/ Linux/ Mac/ Android/ Chrome			
Touch Point	20 points touch			
Touch Tool	Finger, Passive infrared pen			
Minimum Object Size	3mm			
Response Time	≤10ms			
Accuracy	1.5mm	±1.5mm	<1.5mm	±1.5mm
Writing Height	≤3mm	<3mm	<3mm	3mm
Writing Double Colors with Double Simultaneously	Support			
Touch Drive	Free Drive			
Surface Hardness	Toughened Glass with Level 7 of Mohs Standard			
Interpolation Resolution	32,768 (W) × 32,768 (D)			
Android System				
System Version	Android 8.0			
CPU	Dual core A73+Dual core A53			
GPU	Quad core Mali G51			
RAM	3GB			
ROM	16GB			
Power				
Power Requirements	100-240V~ 50/60Hz 5.5A	100-240V~ 50/60Hz	100-240V~ 50/60Hz 3.5A	100-240V~ 50/60Hz 3.0A
Overall Power	550W	350W	350W	300W
Standby Power	≤0.5W			
Physical Specification				
Key Location & Number	Front physical key, 1			
Dimension L × H × D	1,957.2 × 1,160 × 86mm	1,710 × 1,020 × 86mm	1,489 × 897 × 86mm	1,269 × 773 × 86mm
Dimension (Package) L × W × H	2,211 × 280 × 1,370mm	1,860 × 280 × 1,170mm	1,656 × 204 × 1,050mm	1,428 × 220 × 878mm
Thickness of Machine and Wall Mount	126mm (WIB9060F)	132mm (WIB9060F)	116mm (WIB9060G)	116mm (WIB9060G)

Products Specification



Models	L86EE	L75EE	L65EE	L55EE
Physical Specification				
Wall-Hanging Screw Spec	M8 × 25mm			
VESA	800 × 600mm	800 × 400mm	600 × 400mm	400 × 200mm
Net Weight	64.65kg	51.75kg	40.20kg	26.75kg
Gross Weight	95.55kg	70.35kg	51.30kg	34.35kg
Environmental Conditions				
Operations Temperature	0°C - 40°C			
Operation Humidity	10% - 90%RH			
Storage Temperature	-20°C - 60°C			
Storage Humidity	10% - 90%RH			
Altitude	Below 5,000 meter			
Accessories				
Power Cord (European/ American/ British Standard Optional)	× 1 (3 meters)			
USB Touch Cable (Type A-B)	× 1 (5 meters)			
HDMI Cable	× 1 (3 meters)			
Writing Pen	× 2 (SW08)			
Remote Control	× 1			
Battery	× 2 (AAA)			
Random File				
Quick Start Guide	× 1			
Compatible with PC module (Optional)				
Model	MT21/ MT43A	MT21	MT21& MT43A	MT21& MT43A MT43V

Statement

The product pictures of this specification only indicate that there may be slight difference in product effects (included but not limited to appearance, color and size). Please refer to the product. Due to the influence of product configuration and manufacturing process, the actual size/weight of the fuselage may differ.


In order to provide accurate specification parameters and product characteristics as much as possible, it is possible to adjust and revise the text description and picture effect of this specification in real time, so as to match the actual product performance, specifications and other information.

No special notice will be given if necessary.


Products Dimension



Model: L86EE



Model: L75EE



Statement


The product pictures of this specification only indicate that there may be slight difference in product effects (included but not limited to appearance, color and size). Please refer to the product. Due to the influence of product configuration and manufacturing process, the actual size/weight of the fuselage may differ.

In order to provide accurate specification parameters and product characteristics as much as possible, it is possible to adjust and revise the text description and picture effect of this specification in real time, so as to match the actual product performance, specifications and other information.


No special notice will be given if necessary.

Products Dimension

Model: L65EE



Model: L55EE



Statement

The product pictures of this specification only indicate that there may be slight difference in product effects (included but not limited to appearance, color and size). Please refer to the product. Due to the influence of product configuration and manufacturing process, the actual size/weight of the fuselage may differ.

In order to provide accurate specification parameters and product characteristics as much as possible, it is possible to adjust and revise the text description and picture effect of this specification in real time, so as to match the actual product performance, specifications and other information.

No special notice will be given if necessary.